

BICON CABLE GLAND AND CLEAT SELECTOR

FOR PVC/SWA/PVC AND XLPE/SWA/PVC 600/1000 VOLT POWER CABLES

Conductor area mm ²	CABLE SPEC.		GLANDS			Telcleats 385AA	Hook Cleats 371AA	CLEATS		
	Number of cores	BW Indoor	CW Outdoor	E1W E1WF	Aluminium Claw Cleats 370BA			Plastic Cleats LSF E	Nylon Hook Cleats 384AA	
1.5	2	20S	20SS	20SS	1	-	1	0	-	
	3	20S	20SS	20SS	1	-	1	0	-	
	4	20S	20S	20S	1	-	1	0	-	
	7	20S	20S	20S	2	-	2	1	-	
	12	20	20	20	3	-	3	2	-	
	19	25	25	25	4	-	4	3	-	
	27	25	25	25	5	-	5	4	-	
	37	32	32	32	6	5	6	5	-	
2.5	48	32	32	32	6	5	6	5	-	
	2	20S	20S	20S	1	-	2	0	-	
	3	20S	20S	20S	1	-	2	1	-	
	4	20S	20S	20S	2	-	2	1	-	
	7	20	20	20	2	-	3	2	-	
	12	25	25	25	4	-	4	3	-	
	19	25	25	25	5	-	5	4	-	
	27	32	32	32	6	5	6	5	-	
4	37	40	40	40	6	5	6	6	-	
	2	20S	20S	20S	2	-	2	1	-	
	3	20	20	20	2	-	2	1	-	
6	4	20	20	20	3	-	3	2	-	
	2	20	20	20	3	-	3	2	-	
	3	20	20	20	3	-	3	2	-	
10	4	20	20	20	4	-	4	3	-	
	2	25	25	25	4	-	4	3	-	
	3	25	25	25	4	-	4	3	-	
16	4	25	25	25	4	-	5	4	-	
	2	25	25	25	4	-	4	3	-	
	3	25	25	25	4	-	5	4	-	
	4	25	25	25	5	5	6	4	-	
25	2	25	25	25	4	-	4	4	-	
	3	32	32	32	5	5	6	5	-	
	4	32	32	32	5	5	6	5	1	
35	2	32	32	32	5	-	5	5	-	
	3	32	32	32	5	5	6	5	1	
	4	32	32	32	6	5	6	5	1	
50	2	32	32	32	5	5	6	5	1	
	3	32	32	32	6	5	6	5	1	
	4	40	40	40	6	5	6	6	1	
70	2	32	32	32	6	5	6	5	1	
	3	40	40	40	6	6	7	6	1	
	4	40	40	40	7	6	7	7	2	
95	2	40	40	40	6	6	7	6	1	
	3	40	40	40	7	6	7	7	2	
	4	50	50	50S	8	7	8	7	2	
120	2	40	40	40	7	6	7	6	2	
	3	50	50	50S	7	7	8	7	2	
	4	50	50	50	8	8	9	8	3	
150	2	50	50	50S	7	7	8	7	2	
	3	50	50	50S	8	8	9	8	3	
	4	50	50	50	-	9	10	9	3	
185	2	50	50	50S	8	8	9	8	3	
	3	50	50	50	8	9	9	9	3	
	4	63	63	63S	-	9	10	10	4	
240	2	50	50	50	8	8	9	8	3	
	3	63	63	63S	-	9	10	10	4	
	4	63	63	63	-	10	11	11	5	
300	2	63	63	63S	-	9	10	9	3	
	3	63	63	63	-	10	11	11	4	
	4	75	75	75S	-	11	12	12	5	
400	2	63	63	63	-	10	11	10	4	
	3	75	75	75S	-	11	12	12	5	
	4	75	75	75	-	12	13	14	6	

Gland size recommendations only apply to BICON Glands - as stocked by Jointing Technologies