



Scapa 3362

Unbleached Cotton Cloth Tape - 0.29mm

DESCRIPTION

Scapa 3362 is a general purpose unbleached cotton cloth tape with pressure sensitive adhesive. Scapa 3362 is available in a natural colour shade.

APPLICATIONS

- Protective masking and coverings for road "cat's eyes", manhole covers, etc. during roadworks and resurfacing.
- Protection of polished surfaces and machined parts against corrosion.
- Also suitable for use for heavy duty general purpose sealing, packaging, bundling and binding applications.

PRODUCT BENEFITS

- Corrosion resistant.
- Abrasion resistant.
- Flexible and highly conformable.
- Easy tear by hand.
- High initial tack and adhesion.
- Can be written on.
- An economic cloth tape for general purpose applications.
- Service temperature of: -10°C to +60°C.

TECHNICAL PROPERTIES

www.scapaindustrial.com

Technical Property	Nominal Value	Unit	Test Method
Thickness	0.29	mm	AFERA 5006*
Adhesion to Steel	3	N/cm	IEC 60454-2
Tensile Strength	70	N/cm	IEC 60454-2

Version: 7 Generated Date: 16 September 2020

Product Code: 3362

Page: 1 of 2

This Technical Data Sheet (TDS) is provided by Scapa for information only. The contents of this TDS are considered to be reliable but accuracy is not guaranteed. The results shown in this TDS may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Scapa expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect, or consequential) arising from use of the product or reliance on the TDS. Scapa does not exclude liability for death or personal injury arising from its negligence or fraud. Scapa refers to Scapa Group plc and its subsidiaries.

STANDARD PRESENTATIONS

• Roll Length: 25m, 50m

• Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm

· Core: Cardboard

• Packaging: Scapa branded, bulk packed using interleaving sheets between layers.

Note:

Note: Information on stock items, non-standard sizes, and lead times is available on request.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants Shelf life will vary with conditions of use and is affected by climatic environment, but it is recommended that the product should be used within 6 months of date of manufacture, if stored in a moderate climate and good conditions.

Version: 7 Generated Date: 16 September 2020 Page: 2 of 2

www.scapaindustrial.com Product Code: 3362