

Earth electrodes Inspection pits



Lightweight inspection pit

Part no.	Description	Load rating (kg)	Weight each (kg)
PT205	Lightweight inspection pit with grey polymer lid	5000	1.80
PT309-FU	Lightweight inspection pit with black (unbranded) polymer lid	5000	1.80
PT110*	Lightweight inspection pit with concrete lid	1200	7.50

Earth bar for lightweight inspection pit

PT004	5 hole earth bar		0.40
-------	------------------	--	------

Accessories for polymer lid

AK005	6 mm Allen key		0.03
-------	----------------	--	------

Accessories for concrete lid

JH100	M8 x 100 mm long mild steel 'J' bolt lifting hook		0.04
AS100	M8 x 60 stainless steel Allen caphead screw (2 per lid)		0.03

Standards

IEC/BS EN 62561-5

- Manufactured from high-performance, UV stable and chemically resistant polymer with either polymer or concrete lid to suit the application
- The lightweight inspection pit with polymer lid is load rated to 5,000 kg and is suitable for general to heavy duty use. It has a lockable lid and improved working area compared to the concrete inspection pit. The lightweight inspection pit with concrete lid is load rated to 1,200 kg and is designed for use in pedestrianized and light vehicular areas. The lid can be locked in place, if required order 2 x AS100 Allen caphead screws

*Not illustrated (drawing available on request)

