

Industrial Gland Kits

A1/A2 Brass Gland Kit KM409 Series



Application

- > Indoor/Outdoor for Unarmoured Cable

Features & Benefits

- > Brass indoor and outdoor cable gland & accessories
- > For circular, unarmoured plastic or rubber sheathed cables
- > Suitable for most climatic conditions, weatherproof and waterproof
- > Kit comprises:
 - A1/A2 Gland
 - Brass locknut
 - PVC shroud
- > 2 per kit size up to and including 25mm

Technical Data

- > EN 50262
- > BS6121:Pt 1:1989
- > Gland rated to IP66 with use of suitable sealing washer or thread sealant at gland interface
- > Service temperature -20°C to +90°C
- > CuZn39Pb3 extruded brass alloy used for guaranteed strength and performance



Ref: A1A2/03/07

Prysmian Cables & Systems Limited, Components Unit, Oak Road, Wrexham Industrial Estate, Wrexham, LL13 9HP, UK
Commercial Enquiries, Tel +44 (0) 845 767 8345, Fax: +44 (0) 23 8029 5465

www.prysmian.co.uk



WOKING

Unit 19, Woking Business Park, Albert Drive,
Woking GU21 5JY
Tel: 01483 747747 • Fax: 01483 747001


BRISTOL

The Alpha Centre, Armstrong Way, , Great Western
Business Park, Yate, Bristol BS37 5NG
Tel: 01454 322555 • Fax: 01454 323555

NORTON CANES

Unit 15-16, Bellsizes Close, Norton Canes,
Staffordshire WS11 9TQ
Tel: 01543 450555 • Fax: 01543 450600

www.jointingtech.co.uk



Gland Details

Cable Dimensions mm		Kit Reference			Gland Dimensions mm				
Overall Diameter A		Size	Design Number	Items Per Kit	Entry Thread		Approx. Length from Shoulder D mm	Hexagon Size	
Min	Max				Size B	Length C		Across Flats E	Across Corners F
3.5	8.5	20SS	KM409-71	2	M20×1.5	10	20	22.0	24.9
8.0	11.5	20S	KM409-52	2	M20×1.5	10	22	22.0	24.9
11.0	13.5	20	KM409-53	2	M20×1.5	10	22	24.0	26.8
13.0	19.5	25	KM409-55	2	M25×1.5	10	25	30.5	34.0
19.0	25.5	32	KM409-56	1	M32×1.5	10	25	42.4	48.0
25.0	32.0	40	KM409-57	1	M40×1.5	15	33	47.2	53.6
31.5	37.0	50S	KM409-58	1	M50×1.5	15	30	55.0	60.0
36.5	43.0	50	KM409-59	1	M50×1.5	15	30	56.4	61.5
42.5	50.0	63S	KM409-60	1	M63×1.5	15	34	70.1	77.2
49.5	55.0	63	KM409-61	1	M63×1.5	15	32	75.0	83.0
54.5	61.0	75S	KM409-62	1	M75×1.5	15	32	80.0	87.4
60.5	67.0	75	KM409-63	1	M75×1.5	15	40	85.0	95.0

Ref: A1A2/03/07

Prysmian Cables & Systems Limited, Components Unit, Oak Road, Wrexham Industrial Estate, Wrexham, LL13 9HP, UK
Commercial Enquiries, Tel +44 (0) 845 767 8345, Fax: +44 (0) 23 8029 5465

www.prysmian.co.uk



WOKING

Unit 19, Woking Business Park, Albert Drive,
Woking GU21 5JY
Tel: 01483 747747 • Fax: 01483 747001

BRISTOL

The Alpha Centre, Armstrong Way, , Great Western
Business Park, Yate, Bristol BS37 5NG
Tel: 01454 322555 • Fax: 01454 323555

NORTON CANES

Unit 15-16, Bellsizes Close, Norton Canes,
Staffordshire WS11 9TQ
Tel: 01543 450555 • Fax: 01543 450600

www.jointingtech.co.uk