Darcy Spillcare Unit B7 Chaucer Business Park, Watery Lane, Kemsing, Sevenoaks, Kent, TN15 6QY

T +44 (0)1732 762338 F +44 (0)1732 764700



SPECIFICATION FOR DRIZIT® EXTREME OIL ONLY NETTED BOOMS



	0112/NET/1.5	0105/NET/3	0112/NET/3	0112/NET/6
Size	20cm dia x 1.5m	12.5cm dia x 3m	20cm dia x 3m	20cm dia x 6m
Colour	White	White	White	White
Pack Quantity	4	4	4	2
Pack Wt (gross)	10.0 kg	9.2 kg	17.4 kg	17.4 kg
Pack Size	40 dia x 70 cm	70 dia x 60 cm	75 dia x 45 cm	75 dia x 45 cm
Sorbency (pack)	157 - 172 litres	120 - 130 litres	314 - 344 litres	314 - 344 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Outer Casing: Nylon netting.

Inner Casing: Non-woven white polypropylene material.

Filler: Polypropylene or other fibres.

Fitted with: 6mm UV stabilized polypropylene rope along length.

Steel clip and ring for joining

Pack Type: Bag

Compatibility: Water-repellency exceeds requirements of BS 7959-2:2000.

May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents,

mineral oils etc.

Before any use in a spill situation a proper risk assessment should be carried out and all

hazardous properties of the liquid or dangerous reactions taken into account.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and

national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Safety Data Sheet.

This product is non-toxic to users and to aquatic life. Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 08-11-2017

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control

Industrial Marine

