

Conductors

Bare stranded & tinned conductors


3



Standards

BS EN 60228 (soft drawn)

BS EN 7884 (hard drawn)



Bare stranded copper cable

Part no.	Cross-sectional area (mm ²)	Stranding no. / mm ϕ	Nominal diameter (A) (mm)	Weight per metre (kg)
----------	---	---------------------------	---------------------------	-----------------------

Soft drawn stranded copper cable

CB006	6	7/1.04	ϕ 3.12	0.05
CB016	16	7/1.70	ϕ 5.10	0.15
CB025	25	7/2.14	ϕ 6.42	0.23
CB035	35	7/2.52	ϕ 7.56	0.32
CB050-FU	50	19/1.78	ϕ 8.90	0.43
CB070	70	19/2.14	ϕ 10.70	0.62
CB095	95	19/2.52	ϕ 12.60	0.86
CB120	120	37/2.03	ϕ 14.21	1.09
CB150-FU	150	37/2.25	ϕ 15.75	1.33
CB185	185	37/2.52	ϕ 17.64	1.67
CB240	240	61/2.25	ϕ 20.25	2.20
CB300-FU	300	61/2.52	ϕ 22.68	2.76
CB400-FU	400	61/2.85	ϕ 25.65	3.53

Tinned soft drawn stranded copper cable

CB070-T*	70	19/2.14	ϕ 10.70	0.62
----------	----	---------	--------------	------

Hard drawn stranded copper cable

CB071*	70	7/3.55	ϕ 10.70	0.64
--------	----	--------	--------------	------

- *Additional sizes available on request