



IKV TRIBOFOOD XTREME TF SPRAY Anti-Galling Spray



Nonfood Compounds
Program Listed H1
Registration 151862

High Performance *Lubricants* for the *food* industry

DESCRIPTION

IKV TRIBOFOOD X-TREME TF SPRAY is a premium quality, high performance fully synthetic food grade fluid with a PTFE dispersion in an aerosol spray.

IKV TRIBOFOOD X-TREME TF is an NSF H-1 registered product for applications which require a clean lubricant. It is a white and odourless and has a wide temperature range (from -45 to over 200°C).

IKV TRIBOFOOD X-TREME TF SPRAY is an extreme pressure rated anti galling and anti seizing lubricant. It prevents threads seizing and fasteners gallings, it is optimised for use with stainless steel, titanium and aluminium fasteners.

IKV TRIBOFOOD X-TREME TF SPRAY also offers protection against corrosion, dirt and humidity.

IKV TRIBOFOOD X-TREME TF SPRAY offers excellent penetration properties due to its liquid nature and has high dielectric values. It displaces moisture and penetrates in to the most inaccessible equipment areas to provide a durable, long-lasting film.

TYPICAL APPLICATIONS

IKV TRIBOFOOD X-TREME TF SPRAY is widely used in the food industry for the lubrication of chains, cables, slides, pivots, belts, guides, bolts, rollers, bushings, valves and conveyors.

IKV TRIBOFOOD X-TREME TF SPRAY is also equally suitable for non-food applications where a high performance lubricant is required, used as an anti-galling lubricant with both stainless steel, titanium and aluminium fasteners

IKV TRIBOFOOD X-TREME TF SPRAY offers protection from contamination or moisture. It serves as a coating to prevent rust and corrosion where conventional lubricants may fling-off. After the solvent carrier has evaporated off, the high performance synthetic oil and PTFE is left behind as a long-lasting dry film lubricant.



IKV TRIBOFOOD XTREME TF SPRAY Anti- Galling Spray

FEATURES & BENEFITS

- ❖ Premium quality
- ❖ Wide temperature capacity
- ❖ Clean & odourless
- ❖ NSF H1 registered base oil
- ❖ Contains PTFE for long lasting dry lubrication
- ❖ High penetrating capacity
- ❖ Prevents threads seizing and fasteners galling
- ❖ Reduces friction and wear
- ❖ Protects against corrosion, dust and humidity

HEALTH & SAFETY

Use **TRIBOFOOD X-TREME TF SPRAY** in a dry, well-ventilated area.

- ❖ Keep away from combustible materials.
- ❖ Protect eyes and avoid inhalation
- ❖ Pressurized can – do not penetrate or expose to heat or flame – even when empty.
- ❖ Do not smoke when using.

CHARACTERISTIC	PERFORMANCE
Base Fluid	Synthetic
Appearance	Milky white
Solids	PTFE
Specific Gravity	0.837
Temperature Range	-45 to 200°C