

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Standard: UL 224

• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-40°C to +135°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, anti-static, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.



Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H1.2-BLA	Black	300	1.2	0.6	0.36 (±0.10)
H1.6-BLA	Black	300	1.6	0.8	0.36 (±0.10)
H2.4-BLA	Black	150	2.4	1.2	0.45 (±0.10)
H3.2-BLA	Black	150	3.2	1.6	0.45 (±0.10)
H4.8-BLA	Black	60	4.8	2.4	0.56 (±0.10)
H6.4-BLA	Black	60	6.4	3.2	0.56 (±0.10)
H9.5-BLA	Black	60	9.5	4.8	0.56 (±0.10)
H12.7-BLA	Black	60	12.7	6.4	0.56 (±0.10)
H19.1-BLA	Black	60	19.1	9.5	0.70 (±0.10)
H25.4-BLA	Black	30	25.4	12.7	0.90 (±0.15)
H38.1-BLA	Black	30	38.1	19.1	1.00 (±0.15)
H50.8-BLA	Black	25	50.8	25.4	1.10 (±0.20)
H76.2-BLA	Black	25	76.2	38.1	1.46 (±0.20)
H101.6-BLA	Black	25	101.6	50.8	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-BLU	Blue	150	2.4	1.2	0.45 (±0.10)
H3.2-BLU	Blue	200	3.2	1.6	0.45 (±0.10)
H4.8-BLU	Blue	100	4.8	2.4	0.56 (±0.10)
H6.4-BLU	Blue	100	6.4	3.2	0.56 (±0.10)
H9.5-BLU	Blue	100	9.5	4.8	0.56 (±0.10)
H12.7-BLU	Blue	100	12.7	6.4	0.56 (±0.10)
H19.1-BLU	Blue	60	19.1	9.5	0.70 (±0.10)
H25.4-BLU	Blue	30	25.4	12.7	0.90 (±0.15)
H38.1-BLU	Blue	30	38.1	19.1	1.00 (±0.15)
H50.8-BLU	Blue	25	50.8	25.4	1.10 (±0.20)
H76.2-BLU	Blue	25	76.2	38.1	1.46 (±0.20)
H101.6-BLU	Blue	25	101.6	50.8	1.46 (±0.20)
H4.8-BROWN	Brown	100	4.8	2.4	0.56 (±0.10)
H6.4-BROWN	Brown	100	6.4	3.2	0.56 (±0.10)
H9.5-BROWN	Brown	100	9.5	4.8	0.56 (±0.10)
H12.7-BROWN	Brown	60	12.7	6.4	0.56 (±0.10)
H19.1-BROWN	Brown	60	19.1	9.5	0.70 (±0.10)
H25.4-BROWN	Brown	30	25.4	12.7	0.90 (±0.15)
H38.1-BROWN	Brown	30	38.1	19.1	1.00 (±0.15)
H50.8-BROWN	Brown	25	50.8	25.4	1.10 (±0.20)
H76.2-BROWN	Brown	25	76.2	38.1	1.46 (±0.20)
H101.6-BROWN	Brown	25	101.6	50.8	1.46 (±0.20)
H1.2-CLR	Clear	300	1.2	0.6	0.36 (±0.10)
H1.6-CLR	Clear	300	1.6	0.8	0.36 (±0.10)
H2.4-CLR	Clear	150	2.4	1.2	0.45 (±0.10)
H3.2-CLR	Clear	150	3.2	1.6	0.45 (±0.10)
H4.8-CLR	Clear	75	4.8	2.4	0.56 (±0.10)
H6.4-CLR	Clear	60	6.4	3.2	0.56 (±0.10)
H9.5-CLR	Clear	60	9.5	4.8	0.56 (±0.10)
H12.7-CLR	Clear	60	12.7	6.4	0.56 (±0.10)
H19.1-CLR	Clear	60	19.1	9.5	0.70 (±0.10)
H25.4-CLR	Clear	30	25.4	12.7	0.90 (±0.15)
H2.4-GRN	Green	150	2.4	1.2	0.45 (±0.10)
H3.2-GRN	Green	200	3.2	1.6	0.45 (±0.10)
H4.8-GRN	Green	100	4.8	2.4	0.56 (±0.10)
H6.4-GRN	Green	100	6.4	3.2	0.56 (±0.10)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H9.5-GRN	Green	100	9.5	4.8	0.56 (±0.10)
H12.7-GRN	Green	100	12.7	6.4	0.56 (±0.10)
H19.1-GRN	Green	60	19.1	9.5	0.70 (±0.10)
H25.4-GRN	Green	30	25.4	12.7	0.90 (±0.15)
H3.2-G/Y	Green Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-G/Y	Green Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-G/Y	Green Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-G/Y	Green Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-G/Y	Green Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-G/Y	Green Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-G/Y	Green Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-G/Y	Green Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-G/Y	Green Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-G/Y	Green Yellow	25	76.2	38.1	1.46 (±0.20)
H101.6-G/Y	Green Yellow	25	101.6	50.8	1.46 (±0.20)
H4.8-GREY	Grey	100	4.8	2.4	0.56 (±0.10)
H6.4-GREY	Grey	100	6.4	3.2	0.56 (±0.10)
H9.5-GREY	Grey	100	9.5	4.8	0.56 (±0.10)
H12.7-GREY	Grey	60	12.7	6.4	0.56 (±0.10)
H19.1-GREY	Grey	60	19.1	9.5	0.70 (±0.10)
H25.4-GREY	Grey	30	25.4	12.7	0.90 (±0.15)
H38.1-GREY	Grey	30	38.1	19.1	1.00 (±0.15)
H50.8-GREY	Grey	25	50.8	25.4	1.10 (±0.20)
H76.2-GREY	Grey	25	76.2	38.1	1.46 (±0.20)
H101.6-GREY	Grey	25	101.6	50.8	1.46 (±0.20)
H2.4-RED	Red	150	2.4	1.2	0.45 (±0.10)
H3.2-RED	Red	200	3.2	1.6	0.45 (±0.10)
H4.8-RED	Red	100	4.8	2.4	0.56 (±0.10)
H6.4-RED	Red	100	6.4	3.2	0.56 (±0.10)
H9.5-RED	Red	100	9.5	4.8	0.56 (±0.10)
H12.7-RED	Red	100	12.7	6.4	0.56 (±0.10)
H19.1-RED	Red	60	19.1	9.5	0.70 (±0.10)
H25.4-RED	Red	30	25.4	12.7	0.90 (±0.15)
H38.1-RED	Red	30	38.1	19.1	1.00 (±0.15)
H50.8-RED	Red	25	50.8	25.4	1.10 (±0.20)
H76.2-RED	Red	25	76.2	38.1	1.46 (±0.20)

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
H2.4-WHT	White	150	2.4	1.2	0.45 (±0.10)
H3.2-WHT	White	150	3.2	1.6	0.45 (±0.10)
H4.8-WHT	White	75	4.8	2.4	0.56 (±0.10)
H6.4-WHT	White	60	6.4	3.2	0.56 (±0.10)
H9.5-WHT	White	60	9.5	4.8	0.56 (±0.10)
H12.7-WHT	White	60	12.7	6.4	0.56 (±0.10)
H19.1-WHT	White	60	19.1	9.5	0.70 (±0.10)
H25.4-WHT	White	30	25.4	12.7	0.90 (±0.15)
H38.1-WHT	White	30	38.1	19.1	1.00 (±0.15)
H50.8-WHT	White	25	50.8	25.4	1.10 (±0.20)
H76.2-WHT	White	25	76.2	38.1	1.46 (±0.20)
H2.4-YLW	Yellow	150	2.4	1.2	0.45 (±0.10)
H3.2-YLW	Yellow	200	3.2	1.6	0.45 (±0.10)
H4.8-YLW	Yellow	100	4.8	2.4	0.56 (±0.10)
H6.4-YLW	Yellow	100	6.4	3.2	0.56 (±0.10)
H9.5-YLW	Yellow	100	9.5	4.8	0.56 (±0.10)
H12.7-YLW	Yellow	100	12.7	6.4	0.56 (±0.10)
H19.1-YLW	Yellow	60	19.1	9.5	0.70 (±0.10)
H25.4-YLW	Yellow	30	25.4	12.7	0.90 (±0.15)
H38.1-YLW	Yellow	30	38.1	19.1	1.00 (±0.15)
H50.8-YLW	Yellow	25	50.8	25.4	1.10 (±0.20)
H76.2-YLW	Yellow	25	76.2	38.1	1.46 (±0.20)