


- Mains Straight Connector
- Mains Branch

MECHANICAL CONNECTORS

LVMx/SHR Connector



Principle Application:

- ESI 09-8 : Impregnated Paper-Insulated 600/1000 Volt (CONSAC)
- ESI 09-9 : Polymeric Insulated, Combined Neutral/Earth (Waveform)
- BS6346 : PVC Insulated 600/1000 Volt Cable
- BS6480 : Impregnated Paper Insulated Lead or Lead Alloy (PILC)

Range:


Connector Reference (Part Number)	Core C.S.A. (mm ²)			
	Mains		Mains/Branch	
	Min	Max	Min	Max
LVM 1/SHR (51801-75)	70 (1)	95	70 (1)	95
LVM 2/SHR (51801-76)	70 (1)	185	70 (1)	185
LVM 3/SHR (51801-77)	70 (1)	300	70 (1)	300

Note: For jointing other core configurations/sizes please contact Sicame Engineering Department

The Sicame **LVM...** range of connectors has been designed to provide the end user with a cost effective and safe method of jointing all types of LV cables, particularly, in a live 'on-load' jointing situation using a single range of profiled insulated mechanical connectors.

The LVM range of connectors have been tested and witnessed (EA Technology) to confirm their ability to pick up 600 Amps @ 240V.

The LVM connectors are also suitable for jointing an extensive range of LV cables including aluminium or copper, solid or stranded, shaped or circular (service) conductor cores.



JTS/21' Insulated Nut Runner


(See Technical Data Sheet 8.09 for product specification)

- Mains Straight Connector
- Mains Branch

MECHANICAL CONNECTORS

LVM x/SHR Connector

Physical Dimensions



Connector Reference (Part Number)	Dimensions (mm)		
	'A'	'B'	'C'
LVM 1/SHR (51801-75)	80	47	49
LVM 2/SHR (51801-76)	80	57	60
LVM 3/SHR (51801-77)	85	67	70

Material:

Connector Body: Aluminium Alloy (Electro-Tinned)

Connector Shrouds: Polypropelene

Note:

1. Conductor cores of less than 16mm² can be jointed by doubling and re-doubling, where necessary, to achieve a satisfactory cross sectional area.
2. Electro-tinned surface negates the requirement for brass gauze.