

Certifications

Approved by ENEDIS

Section

MV Multifunction

Application

Field

Laboratory

**PRODUCT BENEFITS**

Tuning of the pitch of the tool
 Embedded wear pads to protect the tool from the contact with the outer sheath

TOOL CAPACITY

Diameter 16 - 40 mm
 0,630 - 1,575 inch

Outer sheath and insulation thickness capacity 7 mm / 0,275 mm

TOOL DIMENSIONS

Length 150 mm

Width 80 mm

Height 100 mm

Weight without box 1,24 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
 FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Multifunction tool for outer sheath and insulation

TO DO WHAT

The MF2/40 enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut

Set the length and remove thicker insulation with a straight and neat cut

**Spare part**

KIT-MF3/40 - Protective wear pads

LMF2 - Spare blade for primary insulation

BR - Thrust to set the length of insulation to be remove

VBB1 - Screw for locking the thrust

PCR - Quick set up right angled 45° handle

196855 - Straight handle M10

108098 - Clamping knob for blade

Associated tool

MF1+/25 - Multifunction tool for bonded semiconductor

SRC - Scoring stylus for peelable semiconductor with chamfer

MV cables Tools

MF2/40



Part Number	Diameter	Tool capacity	Dimensions			Packaging
		Outer sheath and insulation thickness capacity	Length	Width	Height	
MF2/40	16 - 40 mm 0,630 - 1,575 in	7 mm / 0,275 mm	150 mm 5,906 in	80 mm 3,150 in	100 mm 3,937 in	box
MF2/40-S	16 - 40 mm 0,630 - 1,575 in	11 mm / 0,433 in	150 mm 5,906 in	80 mm 3,150 in	100 mm 3,937 in	box
MF2/60	16 - 58 mm 0,630 - 2,283 in	7 mm / 0,275 mm	170 mm 6,693 in	90 mm 3,543 in	120 mm 4,724 in	box
MF2/60-S	16 - 58 mm 0,630 - 2,283 in	11 mm / 0,433 in	170 mm 6,693 in	90 mm 3,543 in	120 mm 4,724 in	box