


BUTT AND PARALLEL CONNECTORS



File no. E125401

butt connectors



parallel connectors

PVC insulated

Cond. Size sqmm (AWG)	Ref.	Ø mm	L mm	Quantity Box/Bag
0,2÷0,5 (24÷20)	PL 01-M	3,0	25	3.000/100
0,25÷1,5 (22÷16)	PL 03-M	4,0	25	2.000/100
1,5÷2,5 (16÷14)	PL 06-M	5,0	25	1.500/100
4÷6 (12÷10)	PL 1-M	6,5	32	500/100
0,25÷1,5 (22÷16)	PL 03-P	4,0	20	3.000/100
1,5÷2,5 (16÷14)	PL 06-P	5,0	16	2.000/100

PL




Manufactured from copper tube
 - Electrolytically tin plated
 - The operating temperature range is - 20 to + 80°C (Surge + 90°C).
 - Recommended crimping tools are shown on pages 100 to 107, 135-136.

BUTT CONNECTORS



Polyamide PA6.6 insulated



Cond. Size sqmm (AWG)	Ref.	Øi mm	L mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	NL 03-M	4,0	25,0	2.000/100
1,5÷2,5 (16÷14)	NL 06-M	5,4	25,5	1.500/100
4÷6 (12÷10)	NL 1-M	5,4	32,0	1.000/100
10 (8÷7)	NL 2-M	6,8	43,0	500/100
16 (6÷5)	NL 3-M	7,9	44,0	500/100


NL-M



Manufactured from copper tube
 - Electrolytically tin plated
 - The operating temperature range is - 20 to + 115°C (Surge + 130°C).
 - Recommended crimping tools are shown on pages 100 to 107, 135-136.



PE HD insulated, heat shrinkable



Cond. Size sqmm (AWG)	Ref.	Ø i mm	L1 mm	L2 mm	Quantity Box/Bag
0,5÷1 (20÷17)	WL 03-M	1,7	15,0	36,0	1.500/100
1,5÷2,5 (16÷14)	WL 06-M	2,3	15,0	36,0	1.000/100
4÷6 (12÷10)	WL 1-M	3,4	15,0	41,0	500/100

WL-M




Max operating voltage: 600 V
Shrink temperature: 150 °C
Temperature range: -40 °C to + 105 °C

Manufactured from copper tube
 - Electrolytically tin plated
 - Heat shrink sleeve with sealant
 - Recommended crimping tools are shown on pages 100 to 107.

CLOSE END CONNECTORS



Polyamide PA6.6 insulated



Cond. Size sqmm (AWG)	Ref.	Ø mm	L mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	NL 03P	9,8	21,0	1.000/100
1,5÷2,5 (16÷14)	NL 06-P	7,9	19,9	1.000/100
	NL 06-PB	6,5	13,6	1.500/100
4÷6 (12÷10)	NL 1-P	10,5	21,5	800/100
	NL 1-PG	9,0	17,8	1.000/100

NL-P



Manufactured from copper tube
 - Electrolytically tin plated
 - The operating temperature range is - 20 to + 115°C (Surge + 130°C).
 - Recommended crimping tools are shown on pages 100 to 107, 135-136.

WOKING

Unit 19, Woking Business Park, Albert Drive,
 Woking GU21 5JY
 Tel: 01483 747747 • Fax: 01483 747001

BRISTOL

The Alpha Centre, Armstrong Way, , Great Western
 Business Park, Yate, Bristol BS37 5NG
 Tel: 01454 322555 • Fax: 01454 323555

NORTON CANES

Unit 15-16, Bellsizes Close, Norton Canes,
 Staffordshire WS11 9TQ
 Tel: 01543 450555 • Fax: 01543 450600