



Scapa 167R

Cohesive Friction Tape

DESCRIPTION

Scapa 167 is a black 100% cotton cloth tape, frictioned on both sides with an entirely solvent-free adhesive consisting primarily of synthetic rubber, inorganic fillers, and oil. Previously known in Europe as 2101.

APPLICATIONS

- Spot holding on wire harnesses.
- Secondary wrap for electrical maintenance.

PRODUCT BENEFITS

- Backing material made of 100% cotton cloth.
- Meets the requirements of ASTM D 4514-85.

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesive Thickness (Synthetic Rubber)	9.0 (.229)	Mils (mm)	-
Tensile Strength (ASTM D-1000)	48 (210)	lbs. / inch (N/25mm)	-
Total Thickness (Not Including Liner)	14.0 (.356)	Mils (mm)	-

STANDARD PRESENTATIONS

RECOMMENDATIONS

Application to Surface:

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65°F (18°C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65°F (18°C) or above.

NOTE:1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

2. Shelf life is one year from date of shipment when stored in a cool dry place below 76°F (24°C). Rolls should be stored on end.