


# PKET PKCT



## "TWIN" POLYPROPYLENE INSULATED END SLEEVES

for fine stranded conductors

**HF**  
HALOGEN  
FREE



Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	ND1,ND2,ND3, ND4 and HNKE 50 Compression Aperture	Quantity Box/Bag
		C	B	P	L			
2 x 0,5	PKET508	4,6x2,4	1,8	8,0	15,0	○ white	1	500
2 x 0,75	PKET17508	5,4x2,7	2,1	8,0	15,0	● blue	1,5	500
	PKET7512	5,4x2,7	2,1	12,0	19,0			500
2 x 1	PKET1108	5,3x2,3	2,35	8,0	15,0	● red	2,5	500
	PKET1112	5,3x3,3	2,35	12,0	19,0			500
2 x 1,5	PKET1508	6,5x3,5	2,6	8,0	16,0	● black	2,5	500
	PKET11512	6,5x3,5	2,6	12,0	20,0			500
2 x 2,5	PKET2510	7,7x4,1	3,3	10,0	19,0	○ grey	4	250
	PKET2512	7,7x4,1	3,3	12,0	22,0			250
2 x 4	PKET412	8,7x4,9	4,2	12,0	23,0	● orange	6	100
2 x 6	PKET614	9,9x6,1	5,3	14,0	25,0	● green	10	100
2 x 10	PKET1014	12,9x7,1	6,9	14,0	26,0	● brown	16	100
2 x 16	PKET1616	16,8x9,8	8,9	16,0	31,0	○ white	35	100

Type PKET, PKCT ranges of twin end sleeves are manufactured from Tin plated electrolytic Copper with a purity greater than 99.9%.

Designed to accommodate two cables terminating in the same sleeve they are ideal for looping conductors.

The operating temperature range is - 20 to + 105°C (Surge + 110°C).

Recommended crimping tools are shown on pages 108 to 129, 137-138, 168, 170-171.

Conductor Size sqmm	Type	Dimensions mm				Insulation Colour	ND1,ND2,ND3, ND4 and HNKE 50 Compression Aperture	Quantity Box/Bag
		C	B	P	L			
2 x 0,5	PKCT508	4,6x2,4	1,8	8,0	15,0	● orange	1	500
2 x 0,75	PKCT7508	5,4x2,7	2,1	8,0	15,0	○ white	1,5	500
	PKCT7512	5,4x2,7	2,1	12,0	19,0			500
2 x 1	PKCT1108	5,3x2,3	2,35	8,0	15,0	● yellow	2,5	500
	PKCT1112	5,3x3,3	2,35	12,0	19,0			500
2 x 1,5	PKCT1508	6,5x3,5	2,6	8,0	16,0	● red	2,5	500
	PKCT1512	6,5x3,5	2,6	12,0	20,0			500
2 x 2,5	PKCT2510	7,7x4,1	3,3	10,0	19,0	● blue	4	250
	PKCT2512	7,7x4,1	3,3	12,0	22,0			250
2 x 4	PKCT412	8,7x4,9	4,2	12,0	23,0	○ grey	6	100
2 x 6	PKCT614	9,9x6,1	5,3	14,0	25,0	● black	10	100
2 x 10	PKCT1014	12,9x7,1	6,9	14,0	26,0	○ ivory	16	100
2 x 16	PKCT1616	16,8x9,8	8,9	16,0	31,0	● green	35	100