



Kirk Sandall Industrial Estate, Doncaster, South
Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company
Limited
Reg in England No: 5230722
VAT Reg No: 381 3533 58

TECHNICAL DATA SHEET

PROSOLVE RENDER MESH (PVRMESH1X50)

DESCRIPTION

A premium pink woven alkali-resistant fibreglass reinforcement mesh for render or base coat plaster.

FEATURES:

- Lightweight
- Heavy-duty
- Waterproof – under normal usage
- Versatility – compatible with all popular plasters and renders
- Pressed weave ensures mesh cannot be pulled apart
- Economical – low-cost material with little or no waste
- Durable – tear resistant
- Easy to use – cut to size with a knife or scissors
- Safe – no sharp edges, so no protective clothing is required
- Maintenance-free – tear and alkali resistant with anti-slip properties

SPECIFICATION

WEIGHT: 160gms ± 5

MESH SIZE: 4x4

WEAVE: Leno

LENGTH: 50m

WIDTH: 1m

COLOUR: Pink

LATEX: $\geq 18\%$

TENSILE STRENGTH: Warp $\geq 1500\text{N}/50\text{mm}$ and WEFT $\geq 1600\text{N}/50\text{mm}$

Test methods in conformity with ASTM D1668-94 and ASTM D579-90

NOTE:

The products should be stored at room temperature and kept from wet and heat source.

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.