



Kirk Sandall Industrial Estate, Doncaster, South
Yorkshire, DN3 1QR

+44 (0)1302 310 113
enquiries@prosolveproducts.com
www. prosolveproducts.com

ProSolve is trademark of S.T.L Trading Company
Limited

Reg in England No: 5230722

VAT Reg No: 381 3533 58

TECHNICAL DATA SHEET

ProSolve® Premium Plasterboard Tape (PBT5090P, PBT5090PP, PBT7590P, PBT10090P)

DESCRIPTION

The ProSolve Premium Plasterboard Tape has been developed with adhesion in mind. It has been made with a finer mesh meaning that there is much more adhesive on the rolls than a standard product.

- For drywall joints
- Coating joints
- Professional grade

QUALITY AND PROPERTIES

- Auto adhesive glass meshed tape
- No need to apply first coating for its installation
- Improves resistance between joints and avoid cracks
- Weave: Leno
- Thickness: 0.2mm
- Cloth weight: 55gsm $\pm 5\%$
- Coating: Acrylic Self-Adhesive latex
- Adhesive weight: 75gsm $\pm 5\%$
- Latex: $>28\%$
- Tensile strength: 500 N/500mm

APPLICATION

- Apply a sealing paste or plaster between the two drywall sheets (plasterboard)
- Cut the designed length of ProSolve Premium Plasterboard Tape in order to cover the length of the gap
- Position the tape in the centre of the joint and press firmly
- Plaster over the tape

- Apply a layer of finishing plaster of required

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.